



# GIGAWATT Tarifs Publics Octobre 2023


















## Tarif en euros incluant une TVA à 20%

www.nextaudio.fr













<b>Power Conditioners</b>		<b>SRP</b>
<b>PC-4 EVO+ ver.'21</b> Reference Model. 12 outputs. DC Blocker. Distribution bars - silvered OFC 45 QMM. Internal wiring - silvered OFHC 4 QMM. Hi-Flux Filtering Cores. 2 pole 25A Power Relay (breaking capacity 6500VA). GIGAWATT AUDIO GRADE Suppression Capacitors. Double Power Buffer System. Ultra-rigid, Non Magnetic Aluminium Chassis with Bituminous Vibration Absorber. Voltage Display. C19 Inlet. Rolling-Ball Isolation System		
	with LS-2 EVO cable	<b>13 900</b>
	with LS-1 EVO+ cable	<b>12 700</b>
	with PowerSync ULTRA cable	<b>11 800</b>
<b>PC-3 SE EVO+</b> 6 outputs. DC Blocker. Distribution bars - silvered OFC 30 QMM. Internal wiring - silvered OFHC 4 QMM. Super-MSS Filtering Cores. 16A Relay (breaking capacity 4000VA). Double Power Buffer System. Highly Alloyed Steel Chassis with Bituminous Vibration Absorber. Voltage Display. Solid Aluminum Anti-vibration Feet.		
	with LS-2 EVO cable	<b>9 990</b>
	with LS-1 EVO+ cable	<b>8 690</b>
	with PowerSync ULTRA cable	<b>7 790</b>
<b>PC-3 EVO+</b> 6 outputs. DC Blocker. Distribution bars - OFC 30 QMM. Internal wiring - silvered OFHC 4 QMM. Super-MSS Filtering Cores. 16A Relay (breaking capacity 4000VA). Double Power Buffer System. Highly Alloyed Steel Chassis. Voltage Display. Solid Aluminum Anti-vibration Feet		
	with LS-1 EVO+ cable	<b>7 250</b>
	with PowerSync ULTRA cable	<b>6 350</b>
	with LC-2 EVO cable	<b>5 850</b>
	with PowerSync PLUS cable	<b>5 650</b>
<b>PC-2 EVO+</b> 6 outputs. DC Blocker. Distribution bars - OFC 30 QMM. Internal wiring - OFHC 2,5 QMM. Iron Powder Filtering Cores. 16A Relay (breaking capacity 4000VA). Double Power Buffer System. Highly Alloyed Steel Chassis. Solid Aluminum Anti-vibration Feet.		
	with LS-1 EVO+ cable	<b>6 290</b>
	with PowerSync ULTRA cable	<b>5 390</b>
	with LC-2 EVO cable	<b>4 890</b>
	with PowerSync PLUS cable	<b>4 690</b>
<b>POWERCONTROL</b> 12 outputs. DC Blocker, Distribution bars OFC 30 QMM. Internal wiring OFHC 4,0 QMM. RLC Filtering Block. 16A Relay		
	with LS-1 EVO+ cable	<b>7 590</b>
	with PowerSync ULTRA cable	<b>6 690</b>
	with LC-2 EVO cable	<b>6 190</b>
	with PowerSync PLUS cable	<b>5 990</b>
<b>POWERPRIME</b> 6 outputs. DC Blocker, Distribution bars OFC 30 QMM. Internal wiring OFHC 4,0 QMM. RLC Filtering Block. 16A Relay		
	with PowerSync ULTRA cable	<b>3 790</b>
	with LC-2 EVO cable	<b>3 290</b>
	with PowerSync PLUS cable	<b>3 190</b>

## GIGAWATT Tarifs Publics Octobre 2023

Tarif en euros incluant une TVA à 20%

Power Strips			
<b>PF-2 EVO +</b>			
6 outputs. Metal Shielded Chassis. Distribution bars - OFC 30 QMM. Internal wiring - GigaWatt Powerlink OFHC 4 QMM. Advanced RLC filtering block. Iron Powder Filtering Cores. LED indicators of proper work and polarization.			
		with PowerSync ULTRA cable	<b>2 090</b>
		with LC-2 EVO cable	<b>1 590</b>
		with PowerSync PLUS cable	<b>1 450</b>
<b>PF-1 EVO +</b>			
6 outputs. Metal Shielded Chassis. Distribution bars - OFC 30 QMM. Internal wiring - OFHC 4 QMM. Iron Powder Filtering Cores. LED.			
		with LC-2 EVO cable	<b>990</b>
		with PowerSync PLUS cable	<b>850</b>
		with PowerSync cable	<b>690</b>
<b>PF-1e</b>			
6 outputs. Metal Shielded Chassis. Internal wiring - OFHC 2,5 QMM. Iron Powder Filtering Cores.			
		with PowerSync PLUS cable	<b>650</b>
		with PowerSync cable	<b>550</b>
		without cable	<b>375</b>
Power Cords			
<b>LS-2 EVO</b>			
	Silver plated OFHC, solid-core, twisted conductors. FEP dielectric, Multi Layer PVC external isolation. Copper shielding.		1,5 m <b>3 490</b>
	SE version Loss-free Nano-crystal Alloys Passive Filter. G-050 SM/G-070 SM Metal Body, Rhodium Plated Plugs.		next 0,5 m <b>1 190</b>
<b>LS-1 EVO+</b>			
	Silver plated OFHC, solid-core, twisted conductors. FEP dielectric, Multi Layer PVC external isolation. Copper shielding.		1,5 m <b>2 100</b>
	Loss-free Nano-crystal Alloys Passive Filter. G-015/G-035 Metal Body, Rhodium Plated Plugs.		next 0,5 m <b>690</b>
<b>PowerSync ULTRA</b>			
	8x 1,6 QMM. OFHC multistrand (7 leads) conductors. PE dielectric. PVC external isolation.		1,5 m <b>1150</b>
	Aluminum foil static shield, 100% coverage. G-050SM/G-070SM Metal Body, Rhodium Plated Plugs.		next 0,5 m <b>210</b>
<b>LC-2 EVO</b>			
	7 x 1,5 QMM. OFHC solid-core conductors. PE dielectric. PVC external isolation.		1,5 m <b>550</b>
	Aluminum foil static shield, 100% coverage. G-010/G-030 Rhodium Plated Plugs.		1,0 m <b>505</b>
			next 0,5 m <b>100</b>
<b>PowerSync PLUS</b>			
	3x 2,5 QMM. OFHC multistrand (12 strands per lead). PE dielectric. PVC external isolation.		1,5 m <b>390</b>
	Aluminum foil static shield, 100% coverage. G-010/G-030 Standard Plugs.		1 m <b>350</b>
			next 0,5 m <b>70</b>
<b>PowerSync</b>			
	3x 2.0 QMM. OFHC multistrand (10 strands per lead). PE dielectric. PVC external isolation.		1,5 m <b>290</b>
	Aluminum foil static shield, 100% coverage. G-010/G-030 Standard Plugs.		1 m <b>260</b>
			next 0,5 m <b>45</b>

**GIGAWATT Tarifs Publics Octobre 2023**  
**Tarif en euros incluant une TVA à 20%**

Accessories			
	G-040 SCHUKO for Assembly		35
	G-044 SCHUKO Wall Socket		135
	G-044 Duplex SCHUKO Wall Socket		225
	IEC320-C5 / IEC320-C7 Plug Adapter		35
	LC-Y EVO 3X4 In-Wall Cable (1 meter)		35
	PowerSync Power Supply cable (1 meter)		49
	G-16A Installation Circuit Breaker		190
	G-16A 2P 2-Pole Installation Circuit Breaker		450
	Rolling-Ball Isolation System Anti-Vibration Feet 4 pcs set in a Wooden Box		750
Options			
 	Customized LED display color		90
	Rolling-Ball Isolation System Anti-Vibration Feet for PC conditioners		590